

**IKO****TECHNICAL DATA SHEET****STOCK NO. 4150005****May, 2015****IKO LEADING EDGE PLUS**

Packaged at 18 shingles (x 2 = 36 starter strips) per bundle, each IKO Leading Edge Plus starter strip shingle is perforated down the center to provide two starter strips. IKO Leading Edge Plus is made using our own quality raw materials to ensure optimum roofing quality, and is compatible with all existing IKO shingles. Installation information is printed on the package with easy-to-follow instructions. With IKO Leading Edge Plus, the majority of work is already done for you. Cut to size and perforated down the center, they're fast, easy and simple to apply. IKO's asphalt shingles are produced and designed with consideration for environmental responsibility and sustainability, incorporating quality recycled components whenever possible, manufactured in facilities that comply with the most stringent government environmental regulations, and can therefore be a part of any "green" construction project.

CHARACTERISTIC	UNITS	NOMINAL VALUE	TEST METHOD	STANDARD LIMITS
QUANTITY PER PALLET:	-	45	-	N/A
PALLET SIZE:	cm (in)	101 x 122 (40 x 48)	-	-
LENGTH:	mm (in)	1038 (40 7/8)	-	± 3 (± 1/8)
WIDTH:	mm (in)	200 (7 7/8)	-	± 3 (± 1/8)
HEADLAP:	mm (in)	50 (2)	-	± 3 (± 1/8)
SHINGLES PER PACKAGE:	-	18	-	-
STARTER STRIPS PER SHINGLE	-	2	-	-
COVERAGE PER BUNDLE:	lin. m. (lin. ft.)	37 (123)	-	-

See also Material Information Sheet – MIS # 1213
MIS # 1713

The information on this Technical Data sheet is based upon data considered to be true and accurate, based on laboratory tests and production measurements, and is offered solely for the user's consideration, investigation and verification. Nothing contained herein is representative of a warranty or guarantee for which the manufacturer can be held legally responsible. The manufacturer does not assume any responsibility for any misrepresentation or assumptions the reader may formulate.