

S-700 Thin Spread Floor Tile Adhesive

⚠ CAUTION S-700 EYE AND SKIN IRRITANT

STIR WELL BEFORE USING.

For use with the following Installation Systems:

- Vinyl Composition Tile
- BioBased Tile

DESCRIPTION:

Type:	Water-based/asphalt-rubber
Color:	Black
Taggants:	Contains no visible taggants
Trowel:	S-891 Notched Steel Trowel or S-892 Replaceable Blade Trowel; fine notch (1/32" deep, 1/16" wide, 5/64" apart), U-notch
Coverage:	350–400 sq. ft./gallon (32-37 sq. m.)
Units:	1 gallon (3.78 L) and 4 gallons (15.14 L)
Open Time:	Until dry to touch; approximately 30 minutes or more
Working Time:	18 hours (working times may vary based on job conditions, substrates, temperature, and humidity)
Shelf Life:	1 year, unopened
Freeze/Thaw Stable:	Yes, to 10° F (-12° C)
VOC Content:	Zero g/L; calculated and reported, SCAQMD 1168
Clean Up:	Wet – clean, white cloth with neutral detergent and water Dry – clean, white cloth and mineral spirits
Subfloors:	All grade levels of concrete, ceramic, terrazzo and marble. Polymeric poured floors, suspended wood, and wood underlayments. Steel, stainless steel, aluminum, lead, copper, brass, and bronze. Properly mixed and applied powdered underlayment. Primed and poured-in-place gypsum subfloors. Radiant-heated subfloors where the surface temperature does not exceed 85° F (29° C).
Advantages:	Moisture and alkali resistant AGIS Guarantee Nonflammable, ammonia-free, and low odor Contains low or no organic solvents Can be used over “cutback” adhesive residue (reduces subfloor prep)