



Technical Bulletin

2400 Boston Street, Suite 200, Baltimore, Maryland 21224

Phone: 410-675-2100 or 800-543-3840

Revised: 05/18/07

DAP® KWIK SEAL® Kitchen & Bath Adhesive Caulk

- Cured caulk is mold & mildew resistant
- Waterproof seal
- Paintable
- Easy water clean-up

Packaging: 10.1 fluid ounce (300 mL) cartridge, 5.5 fluid ounce (162 mL) squeeze tube (white only)

Colors: White, Almond

UPC Numbers: 18001, 18012, 18013, 18032, 18002, 71018, 71023, 71050, 71055, 71040

Company Identification:

Manufacturer: DAP Inc., 2400 Boston St., Baltimore, Maryland 21224

Usage Information: DAP HELPLINE: 888-DAP-TIPS, 9:00 am to 7:00 pm EST.

Order Information: 800-327-3339

Fax Number: 410-534-2650

Also, visit the DAP website at www.dap.com.

Product Description:

DAP® KWIK SEAL® Kitchen & Bath Adhesive Caulk is an easy-to-use, all-purpose caulk ideal for caulking and sealing in the bathroom and kitchen. It bonds like a glue and seals like a caulk. It is specially formulated to provide a waterproof seal around tubs, sinks, showers and countertops. Cured caulk is mold and mildew resistant. It offers excellent adhesion, flexibility and durability. It is paintable with either latex or oil-based paint and provides easy water clean-up.

Suggested Uses:

Ideal for caulking and Sealing:

- *Tubs*
- *Showers*
- *Sinks*
- *Countertops*
- *Fixtures*
- *Loose tiles*
- *Backsplashes*
- *Toilets*
- *Cracks & Joints*

Adheres To:

- *Ceramic/plastic tile*
- *Glass*
- *Porcelain*
- *Wood*
- *Metal*
- *Drywall*
- *Fiberglass*
- *Plaster*

Performance Characteristics:

- Cured caulk is mold and mildew resistant.
- Paintable with latex or oil based paints.
- Resists cracking, crumbling and shrinking.
- Does not discolor or yellow.
- Some cleaning products may affect the performance of this product.
- Easy water clean-up.

Surface Preparation & Application:

1. Surface must be clean, dry and free of all old caulk, dirt, dust and grease. Rubbing alcohol is recommended for removing soap film and soil.
2. Remove cap (from tube). Cut nozzle at 45° angle to desired bead size.
3. Load into caulking gun if using the 10.1 oz. cartridge.
4. Fill gap with caulk, pushing caulk ahead of nozzle.
5. For a neat finish, smooth bead of caulk with a finishing tool.
6. Clean up excess caulk with a damp sponge before it skins over (15 minutes).
7. Allow caulk to dry at least 2 hours (longer in cool or humid conditions) before painting with latex or oil-based paint.
8. Wait at least 36 hours before exposing to water or moisture.
9. Reseal tube/cartridge for future use and storage.

For Best Results:

- Caulk in temperatures above 40°F.
- Do not use for below waterline applications. Do not apply product under shower door track or in closed applications.
- Joint width should not exceed 3/8". If joint depth exceeds 3/8", use backer rod material.
- Store caulk away from extreme heat or cold.

Physical & Chemical Characteristics:

Tooling Time:	10 Minutes
Tack Free Time:	15 Minutes
Paintability:	Yes
Odor:	Very mild
Consistency:	Smooth and creamy
Vehicle:	Latex Polymer
Volatile:	Water
Flash Point:	None
Filler:	Calcium Carbonate
Solids:	68 ± 1% by weight
Weight per Gallon:	11.81 ± .05 lbs.
Temperature Service Range:	-20°F to 150°F
Temperature Application Range:	40°F to 100°F
Freeze Thaw Stability:	Passes 5 Cycles 0°F (1 cycle = 16 hrs. @ 0°F, 8 hrs. @ 70°F)
Applications:	Interior
Shelf Life:	1 Year
Coverage:	5.5 fl. oz.: 30 linear ft. at a 3/16" diameter bead 10.1 fl. oz.: 55 linear ft. at 3/16" diameter bead
MSDS No:	00010009001

Clean Up:

Clean up excess uncured caulk with a damp sponge before it skins over (15 minutes). Wash hands with warm water and soap. Dried material must be cut or scraped away.

Safety:

See product label and Material Safety Data Sheet for safety information. You can request an MSDS sheet by visiting our website at www.dap.com or by calling 888-DAP-TIPS.

Satisfaction Guaranteed:

If not satisfied with product performance when used as directed, return used container and sales receipt to DAP Inc., Technical Customer Service, 2400 Boston St., Baltimore, MD, 21224, for product replacement or sales price refund. DAP will not be liable for incidental or consequential damages.