# **SAFETY DATA SHEET**

13618/23618

Section 1. Identification	
---------------------------	--

Product name	: MINWAX WOOD PUTTY®
	Ebony
Product code	: 13618/23618
Other means of	: Not available.
identification	
Product type	: Liquid.
Relevant identified uses of	the substance or mixture and uses advised against
Not applicable.	
Manufacturer	: MINWAX Company
	10 Mountainview Road
	Upper Saddle River, NJ 07458
Emergency telephone	: (216) 566-2917
number of the company	
Product Information	: (800) 523-9299
Telephone Number	
Regulatory Information	: (216) 566-2902
Telephone Number	
Transportation Emergency	: (800) 424-9300
Telephone Number	

# Section 2. Hazards identification

OSHA/HCS status	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	: SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (lungs) - Category 1
GHS label elements	
Hazard pictograms	
Signal word	: Danger
Hazard statements	: Causes damage to organs through prolonged or repeated exposure. (lungs)
Precautionary statements	
General	: Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.
Prevention	<ul> <li>Do not breathe vapor. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling.</li> </ul>
Response	: Get medical attention if you feel unwell.
Storage	: Not applicable.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.

# Section 2. Hazards identification

Supplemental label elements	WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. Adequate ventilation required when sanding or abrading the dried film. If Adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Abrading or sanding of the dry film may release Crystalline Silica which has been shown to cause lung damage and cancer under long term exposure.
	Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.
Hazards not otherwise classified	: DANGER: Rags, steel wool, other waste soaked with this product, and sanding residue may spontaneously catch fire if improperly discarded. Immediately place rags, steel wool, other waste soaked with this product, and sanding residue in a sealed, water-filled, metal container. Dispose of in accordance with local fire regulations.

# Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of	: Not available.
identification	

### **CAS number/other identifiers**

Ingredient name	% by weight	CAS number
Calcium Carbonate	50	471-34-1
Calcium Carbonate	30	1317-65-3
Talc	5	14807-96-6

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

# Section 4. First aid measures

Description of necessary f	<u>t aid measures</u>
Eye contact	<ul> <li>Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention following exposure or if feeling unwell.</li> </ul>
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention following exposure or if feeling unwell. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention following exposure or if feeling unwell. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention following exposure or if feeling unwell. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Date of issue/Date of revision	: 9/7/2017 Date of previous issue : 6/9/2017 Version : 4 2/1

# Section 4. First aid measures

Most important symptoms/effects, acute and delayed				
Potential acute health effe	<u>cts</u>			
Eye contact	: No known significant effects or critical hazards.			
Inhalation	: No known significant effects or critical hazards.			
Skin contact	: No known significant effects or critical hazards.			
Ingestion	: No known significant effects or critical hazards.			
<u>Over-exposure signs/sym</u>	<u>otoms</u>			
Eye contact	: No specific data.			
Inhalation	: No specific data.			
Skin contact	: No specific data.			
Ingestion	: No specific data.			
Indication of immediate me	dical attention and special treatment needed, if necessary			
Notes to physician	<ul> <li>Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.</li> </ul>			
Specific treatments	: No specific treatment.			
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.			

See toxicological information (Section 11)

# Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides
Special protective actions for fire-fighters	<ul> <li>Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.</li> </ul>
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

# Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

personnel Evacuate surrounding areas. Keep unnecessary and unprotected personnel from	For non-emergency personnel	entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is
---	--------------------------------	---

Date of issue/Date of revision	: 9/7/2017	Date of previous issue	: 6/9/2017	Version : 4	3/11
--------------------------------	------------	------------------------	------------	-------------	------

# Section 6. Accidental release measures

- For emergency responders : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- **Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

# Methods and materials for containment and cleaning upSmall spill: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up<br/>if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and<br/>place in an appropriate waste disposal container. Dispose of via a licensed waste<br/>disposal contractor.Large spill: Stop leak if without risk. Move containers from spill area. Approach release from<br/>upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash<br/>spillages into an effluent treatment plant or proceed as follows. Contain and collect<br/>spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or<br/>diatomaceous earth and place in container for disposal according to local regulations<br/>(see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated<br/>absorbent material may pose the same hazard as the spilled product. Note: see<br/>Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

Precautions for safe handling	
Protective measures	: Put on appropriate personal protective equipment (see Section 8). Do not breathe vapor or mist. Do not ingest. Avoid contact with eyes, skin and clothing. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

# Section 8. Exposure controls/personal protection

### **Control parameters**

Occupational exposure limits (OSHA United States)

Ingredient name Exposure limits						
Calcium Carbonate			NIOSH REL (United States, 10/2016). TWA: 5 mg/m <sup>3</sup> 10 hours. Form: Respirable fraction			
Calcium Carbonate			NIOSH REL (U TWA: 5 mg/m fraction	m <sup>3</sup> 10 hours. Form: Tota Inited States, 10/2016). I <sup>3</sup> 10 hours. Form: Respi	rable	
			TWA: 10 mg/	m³ 10 hours. Form: Tota		
Date of issue/Date of revision	: 9/7/2017	Date of previous issue	: 6/9/2017	Version : 4	4/11	

# Section 8. Exposure controls/personal protection

	OSHA PEL (United States, 6/2016).
	TWA: 5 mg/m <sup>3</sup> 8 hours. Form: Respirable
	fraction
	TWA: 15 mg/m <sup>3</sup> 8 hours. Form: Total dust
Talc	NIOSH REL (United States, 10/2016).
	TWA: 2 mg/m <sup>3</sup> 10 hours. Form: Respirable
	fraction
	ACGIH TLV (United States, 3/2016).
	TWA: 2 mg/m <sup>3</sup> 8 hours. Form: Respirable
	fraction

### **Occupational exposure limits (Canada)**

Ingredient name	Exposure limits			
None.				
Occupational exposure limits (Mexico)				

### 

Appropriate engineering controls	:	If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure controls	:	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measur	<u>es</u>	
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection		
Hand protection	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	1	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

# Section 8. Exposure controls/personal protection

# **Section 9. Physical and chemical properties**

<u>Appearance</u>		
Physical state	1	Liquid.
Color	1	Not available.
Odor	1	Not available.
Odor threshold	1	Not available.
рН	1	Not available.
Melting point	1	Not available.
Boiling point	1	Not available.
Flash point	1	Closed cup: >93.3°C (>199.9°F) [Pensky-Martens Closed Cup]
Evaporation rate	1	Not available.
Flammability (solid, gas)	1	Not available.
Lower and upper explosive (flammable) limits	:	Not available.
Vapor pressure	:	Not relevant/applicable due to nature of the product.
Vapor density	:	Not available.
Relative density	:	2.2
Solubility	:	Not available.
Partition coefficient: n- octanol/water	1	Not available.
Auto-ignition temperature	:	Not available.
Decomposition temperature	:	Not available.
Viscosity	:	Kinematic (40°C (104°F)): >0.205 cm²/s (>20.5 cSt)
Molecular weight	:	Not applicable.
Aerosol product		
Heat of combustion	:	3.059 kJ/g

# Section 10. Stability and reactivity

	-
Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Date of issue/Date of revision : 9/7/2017	Date of previous issue	: 6/9/2017	Version : 4	6/11
---	------------------------	------------	-------------	------

**Respiratory protection** 

<sup>:</sup> Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

# Section 11. Toxicological information

### Information on toxicological effects

### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Calcium Carbonate	LD50 Oral	Rat	6450 mg/kg	-

### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Calcium Carbonate	Eyes - Severe irritant	Rabbit	-	24 hours 750 Micrograms	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 milligrams	-
Talc	Skin - Mild irritant	Human	-	72 hours 300 Micrograms Intermittent	-

### **Sensitization**

Not available.

### **Mutagenicity**

Not available.

### **Carcinogenicity**

Not available.

### **Classification**

Product/ingredient name	OSHA	IARC	NTP
Talc	-	3	-

### **Reproductive toxicity**

Not available.

### **Teratogenicity**

Not available.

### Specific target organ toxicity (single exposure)

Not available.

### Specific target organ toxicity (repeated exposure)

Name		Route of exposure	Target organs
Talc	Category 1	Inhalation	lungs

### **Aspiration hazard**

Not available.

Information on the likely routes of exposure	Not ava	ailable.
Potential acute health effe	<u>s</u>	
Eye contact	No kno	wn significant effects or critical hazards.
Inhalation	No kno	wn significant effects or critical hazards.
Skin contact	No kno	wn significant effects or critical hazards.
Ingestion	No kno	wn significant effects or critical hazards.

Date of issue/Date of revision	: 9/7/2017	Date of previous issue	: 6/9/2017	Version : 4	7/11
--------------------------------	------------	------------------------	------------	-------------	------

Symptoms related to the physical, chemical and toxicological characteristics					
Eye contact	: No specific data.				
Inhalation	: No specific data.				
Skin contact	: No specific data.				
Ingestion	: No specific data.				
Delayed and immediate eff	ects and also chronic effects from short and long term exposure				
Short term exposure					
Potential immediate effects	: Not available.				
Potential delayed effects	: Not available.				
Long term exposure					
Potential immediate effects	: Not available.				
Potential delayed effects	: Not available.				
Potential chronic health ef					
Not available.					
General	: Causes damage to organs through prolonged or repeated exposure.				
Carcinogenicity	: No known significant effects or critical hazards.				
Mutagenicity	: No known significant effects or critical hazards.				
Teratogenicity	: No known significant effects or critical hazards.				
Developmental effects	: No known significant effects or critical hazards.				
Fertility effects	: No known significant effects or critical hazards.				

### Numerical measures of toxicity Acute toxicity estimates

Not available.

# Section 12. Ecological information

Toxicity					
Product/ingredient name	Result	Species	Exposure		
Calcium Carbonate	Acute LC50 >56000 ppm Fresh water Chronic NOEC 61 mg/g Fresh water	Fish - Gambusia affinis - Adult Fish - Oncorhynchus mykiss - Juvenile (Fledgling, Hatchling, Weanling)	96 hours 28 days		

### Persistence and degradability

Not available.

### **Bioaccumulative potential**

Not available.

<u>Mobility in soil</u> Soil/water partition coefficient (K <sub>oc</sub> )	: Not available.				
Other adverse effects : No known significant effects or critical					
Date of issue/Date of revision	: 9/7/2017 Date of previous issue : 6/9/2017				

# Section 13. Disposal considerations

Disposal methods	The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
------------------	--

# Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	IATA	IMDG
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-	-
Transport hazard class(es)	-	-	-	-	-
Packing group	-	-	  -	-	-
Environmental hazards	No.	No.	No.	No.	No.
Additional information	-	-	-	-	-

Special precautions for user : Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

Transport in bulk according : Not available. to Annex II of MARPOL and the IBC Code

Proper shipping name Ship type

Pollution category

Not available.Not available.

: Not available.

# Section 15. Regulatory information

### SARA 313


SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet.

### California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

## Section 16. Other information

Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

	Classification	Justification
SPECIFIC TARGET ORG	I TOXICITY (REPEATED EXPOSURE) (lungs) - Ca	ategory Calculation method
<u>History</u>		
Date of printing	: 9/7/2017	
Date of issue/Date of revision	: 9/7/2017	
Date of previous issue	: 6/9/2017	
Version	: 4	
Key to abbreviations	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classif IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goo LogPow = logarithm of the octanol/water partiti MARPOL = International Convention for the Pr as modified by the Protocol of 1978. ("Marpol" UN = United Nations	ods on coefficient evention of Pollution From Ships, 1973

### Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by Sherwin-Williams, including but not limited to the incorporation of non Sherwin-Williams products or the use or addition of products in proportions not specified by Sherwin-Williams. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to

Date of issue/Date of revision : 9/7/2017	Date of previous issue	: 6/9/2017	Version : 4	10/11
---	------------------------	------------	-------------	-------

# Section 16. Other information

determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.