

CRITICAL DIMENSIONS NOT TO SCALE

FEATURES

- TWO ACRYLIC KNOBS
- FITS STANDARD 8" THREE HOLE SINK
- WASHERLESS CARTRIDGE
- FACTORY PRESSURE TESTED

CONSTRUCTION

- METAL CONSTRUCTION WITH POLISHED CHROME FINISH
- PLASTIC VALVE BODIES

MOUNTING

DESIGNED TO INSTALL THROUGH 3 HOLES, 7/8" [23mm] MIN. DIA.
WITH 8" [203mm] CENTERS ON DECKS UP TO 1-1/16" [27mm]

INLET

- 1/2"-14 NPSM THREADED MALE INLET SHANKS
- QUARTER-TURN ACRYLIC KNOB STYLE HANDLES

WATER-CONTROL MECHANISM

- CARTRIDGE
- ROTATING CYLINDER TYPE WITH STAINLESS STEEL PLATE AND NON-METALLIC SEATS

FLOW

AERATOR LIMITS MAXIMUM FLOW RATE TO 2.2 GPM MAX. (8.3 L/MIN.)
@ 60 PSI

CODES/STANDARDS APPLICABLE

- cUPC
- ASME A112.18.1
- ANSI/NSF 61/9
- LOW LEAD COMPLIANT

GUARANTEE

- LIMITED LIFETIME GUARANTEE AGAINST DEFECTS IN MATERIAL AND WORKMANSHIP TO ORIGINAL CONSUMER PURCHASER
- 5 YEAR WARRANTY IF USED IN INDUSTRIAL, COMMERCIAL AND BUSINESS INSTALLATIONS

