

CRITICAL DIMENSIONS NUT TO SCAL

FEATURES

- SINGLE LEVER HANDLE
- FITS STANDARD 8" THREE HOLE SINK
- STAINLESS STEEL BALL VALVE
- FACTORY PRESSURE TESTED
- CONSTRUCTION
- METAL CONSTRUCTION WITH POLISHED CHROME FINISH
- HYBRID VALVE BODY
- MOUNTING
- DESIGNED TO INSTALL THROUGH 3 HOLES, 1-3/16" (30mm) MIN. DIA., ON DECKS UP TO 1-1/8" (29mm)
 INLET
- 0.315" O.D. COPPER TUBE INLETS WITH 1/2"-14 NPSM ADAPTERS **OPERATION**
- PIVOT ACTION LEVER STYLE HANDLE
- OPERATES WITH LESS THAN 5 LBS. OF FORCE

WATER-CONTROL MECHANISM

- ROTATING STAINLESS STEEL BALL TYPE WITH NON-METALLIC SEATS **FLOW**
- AERATOR LIMITS MAXIMUM FLOW RATE TO 2.2 GPM MAX. (8.3 L/MIN.) @ 60 PSI
- **CODES/STANDARDS APPLICABLE**
- ASME A112.18.1
- ANSI/NSF 61/9
- cUPC CERTIFIED
- LOW LEAD COMPLIANT
- GUARANTEE
- LIMITED LIFETIME GUARANTEE AGAINST DEFECTS IN MATERIAL AND WORKMANSHIP TO ORIGINAL CONSUMER PURCHASER
- 5 YEAR WARRANTY IF USED IN INDUSTRIAL, COMMERCIAL AND BUSINESS INSTALLATIONS

