



SEARCH

Products

Resource Center

About

Where to Buy

FPDC20 | EMERGENCY BATTERY BACKUP SUMP PUMP

Home / Flotec Products / FPDC20

Print



Model FPDC20

Emergency Battery Backup Sump Pump

Includes: battery case control unit, 12V pump, reed switch, AC power supply, 1-1/4" NPT to 1-1/2" glue PVC elbow.

Compatible with flooded and sealed AGM deep cycle lead acid batteries.

KEY FEATURES

Basement Flood Protection - Operates automatically during power outage or if primary pump fails.

Proprietary Smart Charging Technology - Recharges battery up to 5X faster and extends battery life.

High Performance Pump - Removes up to 48% more gallons per charge than the leading competitor.

Dual Battery Capacity - Provides extended run time.

WARRANTY

1 year limited warranty

SPECIFICATIONS

RESOURCES

PUMP CONSTRUCTION: Thermoplastic

MAXIMUM FLOW: 2040 GPH

FLOW AT 10' LIFT: 600 GPH

MAXIMUM LIFT: 13.3'

SWITCH TYPE: Reed

MINIMUM SUMP DIAMETER: 14"

MINIMUM SUMP DEPTH: 18"

DISCHARGE PIPE SIZE: 1-1/4"

MINIMUM PIPE SIZE: 1-1/4"

VOLTAGE: 115VAC Charger, 12VDC Backup Pump

RECOMMENDED BREAKER: 15 Amps

LIQUID TEMPERATURE RANGE: 32°F to 70°F (0°C - 21°C)

BATTERY: Compatible with flooded and sealed AGM deep cycle lead acid batteries. For best performance use Flotec BAT40 or BAT75 Sealed AGM batteries.

Performance

PERFORMANCE (GPH)					
DISCHARGE HEIGHT ABOVE PUMPING LEVEL	0'	5'	10'	12'	MAX. LIFT
FPDC20	2040	1300	600	240	13

1

Interactive Guide




VIRTUAL HOUSE

Use our interactive water solutions guide to find products for all your home waterflow needs. Take the tour to see how our products work throughout your home.

[LAUNCH](#)

Contact Us



Call or write to us! We'd love to hear from you.

[CONTACT US](#)
[SITEMAP](#) | [CONTACT US](#) | [BECOME AN AUTHORIZED RETAILER](#)
[TERMS OF SERVICE](#) | [PRIVACY STATEMENT](#)

© 2017 Flotec