


 [SEARCH](#)

- [Products](#)
- [Resource Center](#)
- [About](#)
- [Where to Buy](#)

# FPDC30 | EMERGENCY BATTERY BACKUP SUMP PUMP SYSTEM

[Home](#) / [Flotec Products](#) / [FPDC30](#)

[Print](#)



Model FPDC30

## Emergency Battery Backup Sump Pump System

Protect your most valuable investment!

### KEY FEATURES

- 22% more flow than leading competitor
- 83% more gallons per charge than leading competitor
- Proprietary Smart Charging Technology:** Recharges battery 25% faster and extends battery life
- Link<sub>2</sub>O™ Remote Monitoring:** Constantly monitors system conditions and alerts you (by cell phone or computer) when your basement is in danger of flooding.
- Dual Battery Capacity: Provides extended run time.

### WARRANTY

2 year limited warranty

### SPECIFICATIONS

### RESOURCES

- PUMP CONSTRUCTION:** Thermoplastic
- MAXIMUM FLOW:** 2700 GPH
- FLOW AT 10' LIFT:** 1260 GPH
- MAXIMUM LIFT:** 15'
- SWITCH TYPE:** Reed
- MINIMUM SUMP DIAMETER:** 14"
- MINIMUM SUMP DEPTH:** 18"
- DISCHARGE PIPE SIZE:** 1-1/4"
- MINIMUM PIPE SIZE:** 1-1/4"
- VOLTAGE:** 115v for charger / 12v DC goes out to pump
- RECOMMENDED BREAKER:** 15 Amps
- LIQUID TEMPERATURE RANGE:** 32°F to 70°F (0°C - 21°C)
- BATTERY:** Compatible with flooded and sealed AGM deep cycle lead acid batteries. For best performance use Flotec BAT40 or BAT75 Sealed AGM batteries.

### Performance

PERFORMANCE (GPH)					
DISCHARGE HEIGHT ABOVE PUMPING LEVEL	0'	5'	10'	14'	MAX. LIFT
FPDC30	2700	2040	1260	360	15'

1

### Home Flood Protection



Learn more about our newest Battery Back-Up Sump Pump Systems equipped with Link<sub>2</sub>O™.

[LEARN MORE](#)

### Contact Us



Call or write to us! We'd love to hear from you.

[CONTACT US](#)